

Method Development for Quantification of Activity of Carbon-supported Cu Nanoparticles toward CO₂ Electrocatalysis

Monica Padilla¹, Alexey Serov¹, Zhichao Wang², Albert Epshteyn³, Wenzhen Li² and Olga A. Baturina³

¹University of New Mexico, Albuquerque, NM 87131

²Michigan Technological University,

Houghton MI 49931,

³Naval Research Laboratory, Washington DC 20375

CO₂ is a green-house gas that can be used for production of useful fuels or fuel cell stocks such as methane or ethane [1]. Electrochemical reduction of carbon dioxide to hydrocarbon fuels is one of emerging technologies, with the advantage of being performed under ambient temperature and pressure. As a technology currently in development, it can benefit from accomplishments in the proton exchange membrane fuel cell (PEMFC) technology. The design principles for CO₂ electrolyzers are similar to those of PEMFCs. Similar to the oxygen reduction reaction (ORR) in PEMFCs, the reaction at the cathode of a CO₂ electrolyzer requires a nanoscale catalyst. Contrary to the ORR, CO₂ electroreduction reaction results in multiple reaction products that are generated both in liquid and gas phase. Due to complexity of the system, no method has yet been developed to evaluate the electrocatalytic activities of nanoscale catalysts for reactions that result in multiple reaction products.

Here we report our results on method development for the evaluation of electrocatalytic activity of carbon-supported Cu catalysts for the CO₂ electroreduction reaction. The method involves a combination of the rotating disk electrode (RDE) technique and online gas chromatography (GC). The sealed RDE cell is designed and it is demonstrated that the reaction products generated on small surface area thin RDE films can be quantified by online GC. Liquid reaction products are separated and identified *ex-situ* by liquid chromatography.

Catalysts were synthesized using two different synthetic routes: 1) a nanocapsule method [2] with LiEt₃BH as the reducing agent in benzyl ether and 2) a hydrazine method where N₂H₄ was a reducing agent. Carbon black and 600J Ketjen black were used as catalyst supports. X-Ray diffraction (XRD) and high-resolution transmission electron microscopy (HRTEM) were used for nanoparticles *ex-situ* analysis. The Cu electrochemical surface area was evaluated using Pb underpotential deposition [3].

The particle size of Cu/C catalysts was determined to be *ca.* 30 nm by XRD analysis. The XRD also showed that Cu was partially oxidized to Cu₂O and CuO prior to use in the cell.

For comparison, CO₂ electroreduction reaction products were characterized for Cu films electrodeposited on glassy carbon RDE tips.

Acknowledgements

OAB is grateful to the Office of Naval Research for financial support of this project.

References

- [1] Y. Hori, Electrochemical CO₂ reduction on metal electrodes, in: C.e.a. Vayenas (Ed.) Modern Aspects of Electrochemistry, vol. 42, Springer, New York, 2008.
- [2] Z. Zhang, K.L. More, K. Sun, Z. Wu, W. Li, Chemistry of Materials, 23 (2011) 1570.
- [3] S. Trasatti, O.A. Petrii, Pure and Applied Chemistry, 63 (1991) 711.